PRODUCT INFORMATION



HIGHTEC ZH-M POWER-STEERING-FLUID

High-performance steering gear oil based on mineral base oils for use in hydraulic power steering systems.

Description

HIGHTEC ZH-M POWER-STEERING-FLUID is a steering gear oil from the DEXRON IID generation with outstanding low-temperature performance for use in hydraulic power steering systems.

Application

HIGHTEC ZH-M POWER-STEERING-FLUID has been developed specifically for use in classic hydraulic power steering systems. Its first-rate viscosity-temperature behaviour guarantees safe operation at high steady-state temperatures, as well as a sensitive response at very low temperatures.

The quality of this product is equivalent to EU regulations

- DEXRON IID
- MB 236.3
- VW 009 300
- ZF TE-ML 09

Benefits

- Outstanding viscosity-temperature behaviour and high shear stability
- Sensitive response characteristics, even at extremely low temperatures
- Outstanding ageing and oxidation stability
- · Minimal tendency to foam
- · Neutral behaviour towards gasket materials
- Miscible and compatible with other steering gear oils
 of the same specification. However, in order to exploit
 the full product benefits of HIGHTEC ZH-M
 POWER-STEERING-FLUID, a complete oil change is
 strongly recommended.

Notices

HIGHTEC ZH-M POWER-STEERING-FLUID may not be mixed with glycol or silicone-based fluids (e.g. brake fluids DOT 3/4/5.1 or DOT 5).

Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0.857
Kinematic viscosity KV 40	ASTM D-7042	mm²/s	36
Kinematic viscosity KV 100	ASTM D-7042	mm²/s	7,6
Viscosity index	ASTM D-7042	-	187
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	212
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-41

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guaranty of certain product properties or of the suitability of the product for a specific application. ROWE products are continually improved. Therefore ROWE reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms (www.rowe-oil.com).

ROWE MINERALÖLWERK GMBH Langgewann 101, D-67547 Worms

